

Investigating the Viability of Shape Memory Alloys for Structural Applications

Introduction:

There has been a significant amount of interest in shape memory alloys (SMAs) in recent years because to the extraordinary property that they possess, which is referred to as the shape memory effect. When treated to specific stimuli, like as changes in temperature or stress, SMAs are able to revert to their initial shape as a result of this effect. SMAs have been catapulted to the forefront of engineering research and development as a result of their extraordinary behavior, which differentiates them from conventional materials.


The capability of structural metal alloys (SMAs) to regain their basic shape after being deformed holds a great deal of promise in the field of structural engineering. During the course of their service life, structural components frequently go through a variety of stress, strain, and deformation processes. These processes are caused by a number of causes, including loads, environmental conditions, and structural movement. In the past, rectifying such deformations and restoring structural integrity would have required the implementation of intricate processes or the performance of periodic maintenance interventions. SMAs, on the other hand, provide a solution that is both distinctive and potentially revolutionary.

Engineers are able to take use of the shape memory effect of smart materials assemblies (SMAs) by incorporating them into structural parts. This allows them to automatically correct deformations and ensure that buildings, bridges, pipelines, and other infrastructure continue to preserve their structural integrity. This capacity not only makes the requirements for maintenance easier to manage, but it also improves the structural systems' resilience and reliability. In addition, structural mechanical assemblies (SMAs) have the capability to facilitate the creation of adaptable structures that may dynamically react to shifting environmental conditions or loading scenarios, hence broadening the range of possible applications for these materials in the field of structural engineering.

In addition, the adaptability of SMAs makes it possible to develop technical solutions that are specifically fitted to difficulties. There is a wide range of qualities that can be shown by various types of shape memory alloys (SMAs), including superelasticity, fatigue resistance, and shape memory effect temperatures. Because of this diversity, engineers are able to select structural metal alloys (SMAs) that are the most suitable for the needs of a certain structural application, thereby optimizing both performance and durability.

When taken as a whole, the exceptional capability of SMAs to revert back to their initial structure after being deformed under specific conditions makes them interesting candidates for a wide variety of engineering applications, including structural engineering. The transformational influence that SMAs can have on the design and construction of future infrastructure is highlighted by the fact that they have the ability to ease maintenance, improve resilience, and enable adaptable structures. As research and development in this area continues to grow, it is anticipated that SMAs will play an increasingly important part in the process of defining the built environment.

Objective:

- 
- The purpose of this study is to explore the mechanical properties of various shape memory alloys under a whole range of loading circumstances.
 - To determine the length of time that SMAs are able to withstand structural applications and how well they work over time.
 - Determine whether or not it is possible to incorporate SMAs into the structural systems that are already in place, in order to give guidance for the design and implementation of structural elements that are based on SMA construction.

Literature Review:

The suitability of Shape Memory Alloys (SMAs) for structural applications has been extensively discussed in recent literature, which provides valuable insights into their distinct properties and wide-ranging potential in engineering domains. Petrini and Migliavacca (2011) emphasise the unique attributes of SMAs, including the shape memory effect and pseudo-elastic effect, which serve as the foundation for their exceptional response to external stimuli such as mechanical

loading and temperature fluctuations. SMAs are highly desirable candidates for a diverse range of structural engineering applications due to these fundamental properties.

Furthermore, Casciati et al. (2016) extensively examine the complex array of elements that impact the performance of SMAs, such as loading strain rates, chemical composition, and manufacturing processes. A comprehensive grasp of these complex dynamics is critical in order to fully exploit the capabilities of SMAs in the realm of structural design and optimisation. Furthermore, Miyazaki and Otsuka (1989) establish fundamental principles regarding the martensitic transformation and shape memory mechanism in SMAs, thereby establishing a solid foundation for subsequent investigations and advancements in the domain. The literature further demonstrates the comprehensive investigation of SMAs in various engineering fields. DesRoches and Smith (2004), Janke et al. (2005), and Hartl et al. (2009), respectively, examine the use of SMAs in seismic-resistant design, aerospace applications, and civil engineering structures. The aforementioned studies exemplify the adaptability of SMAs and their capacity to fundamentally transform conventional methodologies for addressing structural engineering dilemmas. Moreover, various scholars have examined SMAs in the context of specialised uses, such as retrofitting concrete, enhancing seismic resistance, and dissipating energy in buildings (Michels et al., 2017; Vignoli et al., 2020; Asfaw and Ozbulut, 2021). Further investigations have examined the application of SMAs in the regulation of vibrations, modification of surface precision, and manipulation of structure shape, as evidenced by the works of Jiang et al. (2019), Zardian et al. (2020), and Barbarino et al. (2008). These studies highlight the multifaceted and inventive methods through which SMAs can make contributions to the field of structural engineering. Furthermore, it is worth noting that the capabilities of SMAs transcend conventional engineering uses. In fact, scholarly investigations have underscored their proper implementation in biomedical contexts and fatigue performance assessments (Huang et al., 2020). This interdisciplinary investigation serves to emphasise the adaptability and versatility of SMAs throughout an array of scientific and engineering fields. In summary, the extensive corpus of scholarly work concerning SMAs establishes a strong basis for additional investigation and application of these materials within the field of structural engineering. The combined results emphasise the considerable capacity of SMAs to improve structural implementations by virtue of their distinctive characteristics and modifiable reactions. Moving forward, it is anticipated that

further investigation and advancement in this field will unveil uncharted territories in the optimisation and design of structural engineering.

Methodology:

The melting process:

Employ vacuum melting methodologies, including vacuum induction melting (VIM) and vacuum arc re-melting (VAR), to achieve controlled melting of the constituent metals (iron, manganese, and silicon). These procedures guarantee the uniformity of the alloy's composition and reduce the risk of impurity contamination.

Treatment by Heat:

To enhance the shape memory characteristics, thermal treatment should be applied subsequent to melting. By subjecting the alloy to cold working prior to thermal treatment, the microstructure can be refined and the shape memory effect can be enhanced. The temperature range of heat treatment generally encompasses 350°C to 550°C, with the precise value contingent upon the alloy's composition and the intended properties.


The utilization of powder metallurgy:

Utilize powder metallurgy methods to fabricate alloy components in a nearly net shape. Compress elemental granules of silicon, manganese, and iron in regulated ratios to produce green compacts. The alloy can be densified and the intended microstructure can be achieved by sintering the green compacts at high temperatures.

Thermostatic Spray:

Utilize thermal spray processes to fabricate thin films or coatings. By utilizing processes such as plasma spraying or flame spraying, the alloy can be applied to substrates. These techniques provide the ability to generate coatings with precise control over their thickness and microstructure to suit particular applications.

Synthetic Thin Film Fabrication:



Thin films composed of should be fabricated via chemical vapor deposition or vacuum sputter deposition. By regulating the deposition parameters, one can attain thin films characterized by accurate chemical compositions and microstructures. Applications for these thin coatings include actuators, sensors, and microelectromechanical systems (MEMS).

In this way different shape memory alloys with optimized properties for a wide range of applications can be synthesized—including structural engineering, biomedical devices, and functional materials.

Anticipated Results:

- An all-encompassing comprehension of the structural reliability and mechanical characteristics of shape memory alloys.
- Design and implementation guidelines for structural elements based on SMA.
- Determination of potential obstacles and domains that warrant additional investigation.

Timeline:

Year 1:

During months one and two, finalize the selection of appropriate shape memory alloys (SMAs) for the study and conduct an exhaustive literature review.

Commence experimental testing in months three through six to determine the mechanical properties of specific SMAs under a variety of loading conditions.


Year 2:

Months 7–9: Proceed with experimental testing and commence an evaluation of the durability of SMAs, encompassing cyclic loading and environmental exposure.

Commence finite element analysis (FEA) in months 10 and 12 to simulate the behavior of structural elements based on SMA.

Year 3:

Months 13-15: Integrate case studies into the research by implementing and monitoring the performance of SMA-based components in real-world structural systems.



ACADEMIC SOLUTIONS

Year 4:

Analyze the data gathered from case studies, FEA, experimental testing, and durability assessment during months 16 and 18.

Compile findings, compose the research report, and defend the PhD dissertation in front of the academic committee during months 19 and 20.

References

- Asfaw, A. and Ozbulut, O. (2021). Characterization of shape memory alloy energy dissipators for earthquake-resilient structures. *Structural Control and Health Monitoring*, 28(4). <https://doi.org/10.1002/stc.2697>
- Barbarino, S., Ameduri, S., Lecce, L., & Concilio, A. (2008). Wing shape control through an sma-based device. *Journal of Intelligent Material Systems and Structures*, 20(3), 283-296. <https://doi.org/10.1177/1045389x08093825>
- Casciati, S., Faravelli, L., & Vece, M. (2016). Investigation on the fatigue performance of ni-ti thin wires. *Structural Control and Health Monitoring*, 24(1), e1855. <https://doi.org/10.1002/stc.1855>
- DesRoches, R. and Smith, B. (2004). Shape memory alloys in seismic-resistant design and retrofit: a critical review of their potential and limitations. *Journal of Earthquake Engineering*, 8(3), 415-429. <https://doi.org/10.1080/13632460409350495>
- Hartl, D., Lagoudas, D., Calkins, P., & Mabe, J. (2009). Use of a ni60ti shape memory alloy for active jet engine chevron application: i. thermomechanical characterization. *Smart Materials and Structures*, 19(1), 015020. <https://doi.org/10.1088/0964-1726/19/1/015020>
- Huang, H., Zhu, Y., & Chang, W. (2020). Comparison of bending fatigue of niti and cualmn shape memory alloy bars. *Advances in Materials Science and Engineering*, 2020, 1-9. <https://doi.org/10.1155/2020/8024803>
- Janke, L., Czaderski, C., Motavalli, M., & Ruth, J. (2005). Applications of shape memory alloys in civil engineering structures—overview, limits and new ideas. *Materials and Structures*, 38(5), 578-592. <https://doi.org/10.1007/bf02479550>
- Jiang, X., Pan, F., Fan, Y., Du, J., Zhu, M., & Chen, Z. (2019). Active adjustment of surface accuracy for a large cable-net structure by shape memory alloy. *Materials*, 12(16), 2619. <https://doi.org/10.3390/ma12162619>

- Michels, J., Shahverdi, M., & Czaderski, C. (2017). Flexural strengthening of structural concrete with iron-based shape memory alloy strips. *Structural Concrete*, 19(3), 876-891. <https://doi.org/10.1002/suco.201700120>
- Miyazaki, S. and Otsuka, K. (1989). Development of shape memory alloys.. *Isij International*, 29(5), 353-377. <https://doi.org/10.2355/isijinternational.29.353>
- Petrini, L. and Migliavacca, F. (2011). Biomedical applications of shape memory alloys. *Journal of Metallurgy*, 2011, 1-15. <https://doi.org/10.1155/2011/501483>
- Vignoli, L., Savi, M., & El-Borgi, S. (2020). Nonlinear dynamics of earthquake-resistant structures using shape memory alloy composites. *Journal of Intelligent Material Systems and Structures*, 31(5), 771-787. <https://doi.org/10.1177/1045389x19898269>
- Zardian, M., Moslemi, N., Mozafari, F., Gohari, S., Yahya, M., Burvill, C., ... & Ayob, A. (2020). Flexural and free vibration control of smart epoxy composite beams using shape memory alloy wires actuator. *Journal of Intelligent Material Systems and Structures*, 31(13), 1557-1566. <https://doi.org/10.1177/1045389x20922899>

